

Digital duplicator

# RISO SF5350 **II** E

**150** ppm High-speed printing

**300x600** dpi High-resolution

**A3** paper size


## Speed Forward Edition II



An upgraded print system for use in various settings

# RISO SF5350 E

## Optional Accessories



RISO FII Type Drum



RISO Auto Document Feeder VII  
Scans multiple documents automatically.



RISO Job Separator IV;  
NIII



Card Feed Kit  
Compatible with paper weight 100 gsm-400 gsm.  
\*Please contact a RISO sales representative for the kinds of paper that may be used.



RISO Stand D Type III  
Deluxe and with doors for convenient storage with a neat appearance.



RISO Stand N Type III  
Sturdy open-front stand also offers convenient storage of consumables.

- IC Card Reader Activation Kit RG
- RISO Printer driver for Macintosh
- Envelope Feed Kit  
Compatible with paper weights 50 gsm to 120 gsm.

## RISO iQualitySystem™



The RISO i Quality mark indicates a RISO product compatible with the RISO i Quality System.



RISO INK FII Type Color (1000 ml)



RISO MASTER FII Type  
(A3: 220 sheets)



RISO INK FII Type Black (1000 ml)

## Specifications

<b>Master Making/Printing Methods</b>		High-speed digital master-making/Fully automatic printing
<b>Original Type</b>		Book or sheet
<b>Master Making Time*1</b>	<b>Quick Master Making mode</b>	- Approx. 14 seconds (A4, long-edge feed) - Approx. 18 seconds (A4, short-edge feed)
	<b>Normal master making mode</b>	- Approx. 16 seconds (A4, long-edge feed) - Approx. 20 seconds (A4, short-edge feed)
<b>Resolution</b>	<b>Scanning</b>	600 dpi × 600 dpi
	<b>Printing</b>	300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi
<b>Maximum Scanning Area</b>		297 mm × 432 mm
<b>Print Paper Weight</b>		46 gsm to 210 gsm
<b>Print Paper Size</b>		100 mm × 148 mm to 310 mm × 432 mm
<b>Maximum Printing Area</b>		291 mm × 413 mm
<b>Paper Feed Tray Stacking Capacity</b>		1000 sheets*2, stacking height of 110 mm or lower
<b>Paper Receiving Tray Stacking Capacity</b>		1000 sheets*2, stacking height of 110 mm or lower
<b>Print Speed</b>		6 levels: 60, 80, 100, 120, 130, and 150 (High Speed *3) ppm
<b>Print Position Adjustment</b>		Horizontal: ±15 mm, Vertical: ±10 mm
<b>Image Processing Mode</b>		Line, Photo, Duo, Pencil
<b>Print Reproduction Ratio</b>		Zoom: (50% to 200%), 100% reduction ratio, 3 levels of enlargement (141%, 122%, 116%), 4 levels of reduction (94%, 87%, 82%, 71%)
<b>User Interface</b>		LCD panel
<b>Functions</b>		Original Scanning mode, Scanning Level, Enlargement/Reproduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF-Semi-Auto*4, Speed, Density, Print Position, Program A/B, D-Feed Check, Slip sheet sorting, Job Separation*5, Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Paper Memory Print, Auto Sleep Setting, Auto Power-OFF Setting, ECO mode, RISO iQuality System
<b>PC Interface</b>		USB2.0, Ethernet:100BASE-TX, 10BASE-T
<b>Ink Supply</b>		Full automatic (1000 ml/cartridge)
<b>Master Supply/Disposal</b>		Full automatic (A3: approx. 220 sheets per roll)/Disposal capacity: approx. 100 sheets
<b>Power Source</b>		AC 100-240 V, 50-60 Hz <3.4-1.6 A>
<b>Power Consumption</b>	<b>Standard</b>	Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.5 W or lower
	<b>Optional Accessories Connected*6</b>	Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.5 W or lower
<b>Dimensions (W×D×H)</b>	<b>In use</b>	1415 mm × 670 mm*7 × 1065 mm*8
	<b>In storage</b>	780 mm × 670 mm*7 × 1065 mm*8
<b>Required Space (W×D×H)</b>		1415 mm × 1240 mm × 1515 mm*8
<b>Weight</b>		101 kg*9

\*1 Measurement value when set to 100% reproduction ratio.

\*2 When using the following weight of paper: 64 gsm to 80 gsm

\*3 If the temperature of the inside of the print drum (cylinder) is less than 5°C, [High Speed] is not usable.

\*4 Usable when the optional auto document feeder is installed.

\*5 Usable when the optional Job Separator is installed.

\*6 When all the following optional accessories are installed, Auto Document Feeder, Job Separator, IC Card Reader.

\*7 The depth does not include the stabilizers for the stand.

\*8 The height includes the stand.

\*9 The weight does not include the ink, master roll, and stand.

Notes: The specifications are subject to change without prior notice.

and RISO, RISO i Quality System and RISO i Quality mark are trademarks or registered trademarks of RISO KAGAKU CORPORATION in the United States and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.  
Copyright ©2019 RISO KAGAKU CORPORATION. All rights reserved.

For more details please contact:



RISO KAGAKU CORPORATION  
5-34-7 Shiba, Minato-ku, Tokyo 108-8385 Japan  
<https://www.riso.com/>