

Digital duplicator

# RISO *SF5350* **ET** E

**150** ppm High-speed printing

**300x600** dpi High-resolution

**A3** paper size

## *Speed Forward Edition II*



An upgraded print system for use in various settings

# RISO SF5350

## Optional Accessories



**RISO FII Type Drum**  
Enables color printing.  
(Case included)



**RISO Auto Document Feeder AF-VII**  
Scans multiple documents automatically.



**RISO Job Separator IV; NIII**  
Enables easy separation of printed sheets by inserting tape strips.



**Card Feed Kit**  
Compatible with paper weight 100 gsm to 400 gsm.  
\*Please contact a RISO sales representative for the kinds of paper that may be used.



**RISO Stand D Type III**  
Deluxe and with doors for convenient storage with a neat appearance.



**RISO Stand N Type III**  
Sturdy open-front stand also offers convenient storage of consumables.

- IC Card Reader Activation Kit RG
- RISO Printer driver for Macintosh
- Envelope Feed Kit  
Compatible with paper weight 50 gsm to 120 gsm.

## RISO iQualitySystem™



The RISO iQuality mark indicates a RISO product compatible with the RISO iQuality System.



**RISO INK FII Type Color (1000 ml)**



**RISO MASTER FII Type**  
(A3: 220 sheets)



**RISO INK FII Type Black (1000 ml)**

## Specifications

|   |  |   |
|---|--|---|
| <b>Master Making/Printing Methods</b>         |  | High-speed digital master-making/Fully automatic printing   |
| <b>Original Type</b>                          |  | Book or sheet   |
| <b>Master Making Time<sup>*1</sup></b>        | <b>Quick Master Making mode</b>                    | - Approx. 14 seconds (A4, long-edge feed)<br>- Approx. 18 seconds (A4, short-edge feed)   |
|   | <b>Normal Master Making mode</b>                   | - Approx. 16 seconds (A4, long-edge feed)<br>- Approx. 20 seconds (A4, short-edge feed)   |
| <b>Resolution</b>                             | <b>Scanning</b>                                    | 600 dpi × 600 dpi   |
|   | <b>Printing</b>                                    | 300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi  |
| <b>Maximum Scanning Area</b>                  |  | 297 mm × 432 mm   |
| <b>Print Paper Weight</b>                     |  | 46 gsm to 210 gsm   |
| <b>Print Paper Size</b>                       |  | 100 mm × 148 mm to 310 mm × 432 mm  |
| <b>Maximum Printing Area</b>                  |  | 291 mm × 413 mm   |
| <b>Paper Feed Tray Stacking Capacity</b>      |  | 1000 sheets <sup>*2</sup> , stacking height of 110 mm or lower  |
| <b>Paper Receiving Tray Stacking Capacity</b> |  | 1000 sheets <sup>*2</sup> , stacking height of 110 mm or lower  |
| <b>Print Speed</b>                            |  | 6 levels: 60, 80, 100, 120, 130, and 150 (High Speed <sup>*3</sup> ) ppm  |
| <b>Print Position Adjustment</b>              |  | Horizontal: ±15 mm, Vertical: ±10 mm  |
| <b>Image Processing Mode</b>                  |  | Line, Photo, Duo, Pencil  |
| <b>Print Reproduction Ratio</b>               |  | Zoom (50% to 200%), 100% reproduction ratio, 3 levels of enlargement (141%, 122%, 116%), 4 levels of reduction (94%, 87%, 82%, 71%)   |
| <b>User Interface</b>                         |  | LCD panel   |
| <b>Functions</b>                              |  | Original Scanning Mode, Scanning Level, Enlargement/Reduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF Semi-Auto <sup>*4</sup> , Speed, Density, Print Position, Program A/B, D-Feed Check, Slip Sheet Sorting, Job Separation <sup>*5</sup> , Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Paper Memory Print, Auto Sleep Setting, Auto Power-OFF Setting, ECO Mode, RISO iQuality System |
| <b>PC Interface</b>                           |  | USB2.0, Ethernet:100BASE-TX, 10BASE-T   |
| <b>Ink Supply</b>                             |  | Full automatic (1000 ml/cartridge)  |
| <b>Master Supply/Disposal</b>                 |  | Full automatic (A3: approx. 220 sheets per roll)/Disposal capacity: approx. 100 sheets  |
| <b>Power Source</b>                           |  | AC 100-240 V, 50-60 Hz <3.4-1.6 A>  |
| <b>Power Consumption</b>                      | <b>Standard</b>                                    | Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.3 W or lower   |
|   | <b>Optional Accessories Connected<sup>*6</sup></b> | Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.3 W or lower  |
| <b>Dimensions (W×D×H)</b>                     | <b>In use</b>                                      | 1415 mm × 670 mm <sup>*7</sup> × 1065 mm <sup>*8</sup>  |
|   | <b>In storage</b>                                  | 780 mm × 670 mm <sup>*7</sup> × 1065 mm <sup>*8</sup>   |
| <b>Required Space (W×D×H)</b>                 |  | 1415 mm × 1240 mm × 1515 mm <sup>*8</sup>   |
| <b>Weight</b>                                 |  | 101 kg <sup>*9</sup>  |

<sup>\*1</sup> Measurement value when set to 100% reproduction ratio.

<sup>\*2</sup> When using the following weight of paper; 64 gsm to 80 gsm

<sup>\*3</sup> If the temperature of the inside of the print drum (cylinder) is less than 5°C, [High Speed] is not usable.

<sup>\*4</sup> Usable when the optional auto document feeder is installed.

<sup>\*5</sup> Usable when the optional Job Separator is installed.



<sup>\*6</sup> When all the following optional accessories are installed; Auto Document Feeder, Job Separator, IC Card Reader.

<sup>\*7</sup> The depth does not include the stabilizers for the dedicated stand.

<sup>\*8</sup> The height includes the dedicated stand.

<sup>\*9</sup> The weight does not include the ink, master roll, and stand.

Notes: The specifications are subject to change without prior notice.

 and , RISO iQuality System and RISO iQuality mark are trademarks or registered trademarks of RISO KAGAKU CORPORATION in the United States and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.  
Copyright ©2019 RISO KAGAKU CORPORATION. All rights reserved.



**RISO KAGAKU CORPORATION**  
5-34-7 Shiba, Minato-ku, Tokyo 108-8385 Japan  
<https://www.riso.com/>

For more details please contact: